

# SAFETY DATA SHEET

## NST MIG/TIG ERNiCrMo-3/13

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name** NST MIG/TIG ERNiCrMo-3/13  
**Synonyms, trade names** NST MIG ERNiCrMo-3 , NST TIG ERNiCrMo-3, NST MIG ERNiCrMo-13(A59), NST TIG ERNiCrMo-13(A59)

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Applications** Welding wire

#### 1.3. Details of the supplier of the safety data sheet

**Supplier** Norsk Sveiseteknikk AS  
Postboks 575  
NO-3002 Drammen, Norway  
Tel: +47 99 27 80 00  
Fax: +47 32 82 90 19  
E-mail: nst@nst.no  
www.nst.no

**Contact person** Eyvind Røed (E-mail: eyvind@nst.no)

#### 1.4. Emergency telephone number

**Emergency telephone number** 112 / The UK National Poisons Emergency number: +44 870 600 6266

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

**Classification according to directives 67/548/EEC, 99/45/EC & 2001/58/EC (DSD/DPD)** Xn, R-40  
Xi, R-43  
T, R-48/23

**Classification according to directive 1272/2008 (CLP)** GHS08, GHS07, Danger  
Skin Sens. 1: H317  
Carc. 2: H351  
STOT RE 1: H372

**Hazard** Metals in massive form and alloy do not require a label according to EU-Regulation 1272/2008, section 1.3.4.

#### 2.2. Label elements

CLP

Hazard pictograms



|  |  |
|--|--|
| <b>Signal word</b>   | Danger   |
| <b>Hazard statements</b>                                       | Skin Sens. 1: H317 May cause an allergic skin reaction.<br>Carc. 2: H351 Suspected of causing cancer .<br>STOT RE 1: H372 Causes damage to organs through prolonged or repeated exposure .   |
| <b>Precautionary statements</b>                                | P260 Do not breathe dust/fume/gas/mist/vapours/spray.<br>P271 Use only outdoors or in a well-ventilated area.<br>P280 Wear protective gloves/protective clothing/eye protection/face protection.<br>P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.<br>P333+P313 If skin irritation or rash occurs: Get medical advice/attention. |
| <b>Contains</b>  | nickel (Ni)<br>chromium (Cr)   |
| <b>2.3. Other hazards</b>                                      |  |
| <b>Meets the criteria for vPvB</b>                             | No.  |
| <b>Meets the criteria for PBT</b>                              | No.  |
| <b>Other hazards which do not contribute to classification</b> | No known risks.  |

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### Ingredients

| Name            | EC No.    | CAS No.   | Content | Symbol | Classification      |
|-----------------|-----------|-----------|---------|--------|---------------------|
| iron (Fe)       | 231-095-1 | 7439-89-6 | 50-60 % | -      |                     |
| nickel (Ni)     | 231-111-4 | 7440-02-0 | 35-99 % | T      | R-40, R-43, R-48/23 |
| chromium (Cr)   | 231-157-5 | 7440-47-3 | 5-24 %  | -      |                     |
| manganese (Mn)  | 231-105-1 | 7439-96-5 | <1 %    | -      |                     |
| silicon (Si)    | 231-130-8 | 7440-21-3 | <2 %    | -      |                     |
| molybdenum (Mo) | 231-107-2 | 7439-98-7 | <30 %   | -      |                     |
| niobium (Nb)    | 231-113-5 | 7440-03-1 | <5 %    | -      |                     |
| copper (Cu)     | 231-159-6 | 7440-50-8 | <30 %   | -      |                     |
| aluminium (Al)  | 231-072-3 | 7429-90-5 | <2 %    | -      |                     |
| titanium (Ti)   | 231-142-3 | 7440-32-6 | 3,5 %   | -      |                     |
| vanadium (V)    | 231-171-7 | 7440-62-2 | <0,6 %  | -      |                     |
| Tungsten        | 231-143-9 | 7440-33-7 | <4,5 %  | -      |                     |

#### CLP

| Name            | REACH No.            | Content | Symbol                    | Classification  | CAS No.   |
|-----------------|----------------------|---------|---------------------------|---|-----------|
| iron (Fe)       | 01-211946283<br>8-24 | 50-60 % |                           |   | 7439-89-6 |
| nickel (Ni)     | 01-211943872<br>7-29 | 35-99 % | GHS08, GHS07,<br>, Danger | Skin Sens. 1:<br>H317, Carc. 2:<br>H351, STOT RE<br>1: H372 | 7440-02-0 |
| chromium (Cr)   | 01-211948565<br>2-31 | 5-24 %  |                           |   | 7440-47-3 |
| manganese (Mn)  | 01-211944980<br>3-34 | <1 %    |                           |   | 7439-96-5 |
| silicon (Si)    | 01-211948040<br>1-47 | <2 %    |                           |   | 7440-21-3 |
| molybdenum (Mo) | 01-211947230<br>4-43 | <30 %   |                           |   | 7439-98-7 |
| niobium (Nb)    | 01-211948900<br>3-42 | <5 %    |                           |   | 7440-03-1 |
| copper (Cu)     | 01-211948015<br>4-42 | <30 %   |                           |   | 7440-50-8 |
| aluminium (Al)  | 01-211952924<br>3-45 | <2 %    |                           |   | 7429-90-5 |
| titanium (Ti)   | 01-211948487<br>8-14 | 3,5 %   |                           |   | 7440-32-6 |
| vanadium (V)    |                      | <0,6 %  |                           |   | 7440-62-2 |
| Tungsten        |                      | <4,5 %  |                           |   | 7440-33-7 |

**Composition comments**

By classification of the solid product is only the properties of physical contact and environment included. In the smoke emitted by use, there will be an additional risk by inhalation. Intensive exposure to welding fumes can cause lung disease, bronchitis, or worsen already existing inhalation problems. Intensified exposure to Manganese (Mn) can damage the central nervous system or worsen existing health problems.

Section 16 contains detailed classification phrases.

**SECTION 4: First aid measures****4.1. Description of first aid measures****General**

Remove victim immediately from source of exposure. Provide rest, warmth and fresh air. Get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed****Specific first aid treatment**

Electric shock: Disconnect and turn off power. If the victim is semi- or unconscious, open the airway. If the victim cannot breathe, give artificial respiration. If there is no pulse, massage the chest and apply artificial respiration.

**4.3. Indication of any immediate medical attention and special treatment needed****Inhalation**

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues. Alternatively artificial respiration.

**Ingestion**

Rinse nose, mouth and throat with water.

**Skin**

Wash skin with soap and water. At burns, cool skin with ice or cold water. Get medical attention if any discomfort continues.

**Eyes**

Rinse with water. Contact physician if discomfort continues. Make sure to remove any contact lenses from the eyes before rinsing. Do not rub eye.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Extinguishing media**

Use extinguishing media appropriate for surrounding fire.

**Special fire fighting procedures**

Avoid breathing fire vapours.

**5.2. Special hazards arising from the substance or mixture**

**Specific hazards** Non-flammable.

**Hazardous combustion products** Fire or high temperatures create: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).  
@@@Oksyder av Krom, Nikkel, Jern, Mangan, Silisium, Niob, Kopper, Aluminium, Titan, Vanadium.@@@

**5.3. Advice for firefighters**

**Protective measures in fire** Firefighters exposed to combustion gases/decomposition products should use a respiratory protective device.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

**Personal protection** Ventilate well. Use requisite protective equipment - refer to section 8. Avoid contact with skin, eyes and inhalation of vapours.

**6.2. Environmental precautions**

**Environmental protection** Prevent discharge of larger quantity to drain.

**6.3. Methods and material for containment and cleaning up**

**Spill cleanup methods** Limit spread of spilled material. Prevent discharge to drainage systems. Carefully collect larger quantities into closed container.

**6.4. Reference to other sections**

See section 13 for waste handling.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling**

**Usage precautions** Provide good ventilation. Use mechanical ventilation in case of handling which causes formation of vapours. Avoid inhalation of vapours. Avoid spilling, skin and eye contact. Do not touch live electrical parts such as the welding wire and welding machine terminals. Wear insulated gloves and safety boots.

**7.2. Conditions for safe storage, including any incompatibilities**

**Storage precautions** Keep in cool, dry, ventilated storage and closed containers. Keep away from moisture.

**7.3. Specific end use(s)**

**Specific use(s)** Contact supplier for more information.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters**

| Ingredient name | CAS no.   | Reference | LT Exp 8 Hrs  | ST Exp 15 Min                     | Date |
|-----------------|-----------|-----------|---|-----------------------------------|------|
| nickel (Ni)     | 7440-02-0 | WEL.      | 0.5 mg/m <sup>3</sup> (Sk)                              |                                   |      |
| chromium (Cr)   | 7440-47-3 | WEL.      | 0,5 mg/m <sup>3</sup>                                   |                                   |      |
| manganese (Mn)  | 7439-96-5 | WEL.      | 0,5 mg/m <sup>3</sup>                                   |                                   |      |
| silicon (Si)    | 7440-21-3 | WEL.      | 10 / 4 mg/m <sup>3</sup> ,<br>inhalable/respirable dust |                                   |      |
| molybdenum (Mo) | 7439-98-7 | WEL.      | 10 mg/m <sup>3</sup>                                    | 20 mg/m <sup>3</sup>              |      |
| copper (Cu)     | 7440-50-8 | WEL.      | 0,2/1 mg/m <sup>3</sup> ,<br>fume/dust                  | 2 mg/m <sup>3</sup> total<br>dust |      |

**Ingredient comments** WEL = Workplace exposure limits. SK= Skin absorbance, Rep= Reproduction, Carc= Carcinogenic, Senz= Sensitisers, Mut= Carcinogenic

**Protective equipment**



|                                |   |
|--------------------------------|---|
| <b>Process conditions</b>      | Provide eyewash station. It is forbidden to weld in rooms with halogenated solvents in the working atmosphere.  |
| <b>Ventilation</b>             | Well ventilated area. Working operations which cause formation of high volumes of vapour should take place in ventilation hood or with local exhaust ventilation.   |
| <b>8.2. Exposure controls</b>  |   |
| <b>Respirators</b>             | At work in confined or poorly ventilated spaces, respiratory protection with air supply must be used. Standard EN 149.  |
| <b>Protective gloves</b>       | Chemical resistant gloves required for prolonged or repeated contact. Wear insulated protection gloves designed for welding. EN 374 standard.   |
| <b>Eye protection</b>          | Wear approved safety glasses with high protection factor against UV-radiation. Wear helmet or use face shield with filter lens. As a rule of thumb, start with a shade which is too dark to see the weld zone. Then go to the next lighter shade which gives sufficient view of the weld zone. Provide protective screens and flash goggles, if necessary, to shield others. EN 166 standard. |
| <b>Other Protection</b>        | Wear appropriate clothing to prevent any possibility of skin contact.<br>Wear earplugs or earmuffs when using engine or pulsed driven arc welding machines that generates high-level noise.   |
| <b>Hygienic work practices</b> | Wash at the end of each work shift and before eating, smoking and using the toilet. Eating, smoking and water fountains prohibited in immediate work area.  |
| <b>DNEL</b>                    | No data.  |
| <b>PNEC</b>                    | No data.  |

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

|  |   |
|--|---|
| <b>Appearance</b>                            | Wire  |
| <b>Colour</b>                                | Copper. Metallic.                               |
| <b>Odour</b>                                 | Odourless or no characteristic odour.           |
| <b>Solubility description</b>                | Insoluble in water.<br>Soluble in strong acids. |
| <b>Melting/freezing point (°C, interval)</b> | Ca. 1600  |
| <b>Density (g/cm<sup>3</sup>)</b>            | Ca. 7,0   |
| <b>9.2. Other information</b>                | <b>Temperature (°C)</b>                         |

|                               |            |
|-------------------------------|------------|
| <b>9.2. Other information</b> |            |
| <b>Safety information</b>     | Not known. |

## SECTION 10: Stability and reactivity

|   |   |
|---|---|
| <b>10.1. Reactivity</b>                         | No incompatible groups noted.                                   |
| <b>10.2. Chemical stability</b>                 | Stable under normal temperature conditions and recommended use. |
| <b>10.3. Possibility of hazardous reactions</b> |   |
| <b>Hazardous polymerisation</b>                 | Will not polymerise.  |
| <b>10.4. Conditions to avoid</b>                | Water, moisture.  |
| <b>10.5. Incompatible materials</b>             |   |

|   |  |
|---|--|
| <b>Materials to avoid</b>                     | Acids, may generate gases.   |
| <b>10.6. Hazardous decomposition products</b> |  |
| <b>Hazardous decomp. products</b>             | Hazard decomposition products includes those from the volatilization, reaction or oxidation of the materials listed in the composition, and those from the base metal and coating. |

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

|                                  |   |
|----------------------------------|---|
| <b>Sensitization</b>             | May cause an allergic skin reaction.  |
| <b>Genotoxicity</b>              | No known heritable or mutagenic effects.  |
| <b>Carcinogenicity</b>           | Limited evidence of a carcinogenic effect. Long term and repeated inhalation of gases from welding may pose and increased risk of acquiring cancer related lung diseases.   |
| <b>Reproduction toxicity</b>     | No known hazardous effects on reproduction, fertility or to the unborn child.   |
| <b>Toxicological information</b> | The product in its normal state represents no toxic risks, but the smoke emitted by welding poses an additional risk by inhalation. Overexposure to welding fumes may result in symptoms like dizziness, nausea, dryness or irritation of the nose, throat and eyes.            |
| <b>Inhalation</b>                | Toxic: danger of serious damage to health by prolonged exposure through inhalation. Gas or vapour in high concentrations may irritate respiratory system. Overexposure to welding fumes may affect pulmonary function. Overexposure to manganese may affect the nervous system. |
| <b>Ingestion</b>                 | Ingestion is not a likely route of exposure, the product is supplied as an wire.  |
| <b>Skin</b>                      | Prolonged or repeated contact leads to drying of skin.  |
| <b>Eyes</b>                      | Vapour, spray or dust may cause chronic eye irritation or eye damage.   |
| <b>COMPONENT:</b>                | <b>iron (Fe)</b>  |
| <b>Toxic dose - LD50:</b>        | 30000 mg/kg (oral rat)  |
| <b>COMPONENT:</b>                | <b>nickel (Ni)</b>  |
| <b>Toxic dose - LD50:</b>        | >5000 mg/kg (oral rat)  |
| <b>Toxic dose - LD50 (skin):</b> | >2000 mg/kg (skin rabbit)   |
| <b>COMPONENT:</b>                | <b>manganese (Mn)</b>   |
| <b>Toxic dose - LD50:</b>        | 9000 mg/kg (oral rat)   |
| <b>COMPONENT:</b>                | <b>silicon (Si)</b>   |
| <b>Toxic dose - LD50:</b>        | 3160 mg/kg (oral rat)   |
| <b>COMPONENT:</b>                | <b>niobium (Nb)</b>   |
| <b>Toxic dose - LD50:</b>        | >10 mg/kg (oral rat)  |
| <b>COMPONENT:</b>                | <b>copper (Cu)</b>  |
| <b>Toxic dose - LD50:</b>        | 1120 mg/kg (oral rat)   |
| <b>Toxic dose - LD50 (skin):</b> | 2000 mg/kg (skin rabbit)  |
| <b>Toxic conc. - LC50:</b>       | 1300 mg/m <sup>3</sup> (inh-rabbit)   |
| <b>COMPONENT:</b>                | <b>Tungsten</b>   |
| <b>Toxic dose - LD50:</b>        | >2000 mg/kg (oral rat)  |
| <b>Toxic dose - LD50 (skin):</b> | >2000 mg/kg (skin rat)  |
| <b>Toxic conc. - LC50:</b>       | >5,4 mg/kg/4t (inh-rat)   |

## SECTION 12: Ecological information

### 12.1. Toxicity

|                    |   |
|--------------------|---|
| <b>Ecotoxicity</b> | No negative effects on the aquatic environment are known. |
|--------------------|---|

### 12.2. Persistence and degradability

The chemical is not readily biodegradable.

### 12.3. Bioaccumulative potential

Not relevant, inorganic components.

**12.4. Mobility in soil**

**Mobility** Insoluble in water.

**12.5. Results of PBT and vPvB assessment**

**PTB/vPvB** Component(s) is not identified as PBT or vPvB substance(s).

**12.6. Other adverse effects**

No known adverse affects.

**COMPONENT:**

**LC 50, 96 Hrs, Fish mg/l:**

**EC 50, 48 Hrs, Daphnia, mg/l:**

**IC 50, 72 Hrs, Algae, mg/l:**

**Bioaccumulative potential**

**COMPONENT:**

**LC 50, 96 Hrs, Fish mg/l:**

**EC 50, 48 Hrs, Daphnia, mg/l:**

**IC 50, 72 Hrs, Algae, mg/l:**

**Bioaccumulative potential**

**Partition coefficient (log Pow)**

**COMPONENT:**

**LC 50, 96 Hrs, Fish mg/l:**

**EC 50, 48 Hrs, Daphnia, mg/l:**

**IC 50, 72 Hrs, Algae, mg/l:**

**Bioaccumulative potential**

**COMPONENT:**

**LC 50, 96 Hrs, Fish mg/l:**

**EC 50, 48 Hrs, Daphnia, mg/l:**

**IC 50, 72 Hrs, Algae, mg/l:**

**Bioaccumulative potential**

**COMPONENT:**

**LC 50, 96 Hrs, Fish mg/l:**

**EC 50, 48 Hrs, Daphnia, mg/l:**

**IC 50, 72 Hrs, Algae, mg/l:**

**Bioaccumulative potential**

**COMPONENT:**

**LC 50, 96 Hrs, Fish mg/l:**

**EC 50, 48 Hrs, Daphnia, mg/l:**

**IC 50, 72 Hrs, Algae, mg/l:**

**Bioaccumulative potential**

**Partition coefficient (log Pow)**

**COMPONENT:**

**LC 50, 96 Hrs, Fish mg/l:**

**COMPONENT:**

**LC 50, 96 Hrs, Fish mg/l:**

**EC 50, 48 Hrs, Daphnia, mg/l:**

**IC 50, 72 Hrs, Algae, mg/l:**

**Bioaccumulative potential**

**iron (Fe)**

13,6 (Morone saxatilis, FeCl<sub>2</sub>)

5,2 (Daphnia magna)

0,1

BCF:140000

**nickel (Ni)**

>100 (Brachydanio rerio)

>100 (Daphnia magna)

0,18 (Selenastrum capricornutum)

BCF:16

<0

**chromium (Cr)**

3,4 (Oncorhynchus mykiss)

0,02 (Daphnia pulex)

0,001

BCF:200

**manganese (Mn)**

2,91

5,2 (Daphnia magna)

0,55

BCF:59052

**copper (Cu)**

0,017 (Oncorhynchus mykiss)

0,2 (Daphnia magna, water flea)

0,392 (Selenastrum)

BCF:29

**aluminium (Al)**

>100

>100 (Daphnia magna)

>100

BCF:18

<3

**titanium (Ti)**

7,31

**vanadium (V)**

0,17

0,8

0,5

BCF:2

**SECTION 13: Disposal considerations****13.1. Waste treatment methods**

**General/cleaning** Waste is classified as hazardous waste.

**Disposal methods** Collect in marked containers and deliver to approved depot.

**Waste class** 12 01 13 welding wastes

## SECTION 14: Transport information

|  |   |
|--|---|
| <b>General</b>   | No dangerous goods (ADR/RID, IMDG, IATA/ICAO)     |
| <b>14.1. UN number</b>   |   |
| <b>14.2. UN proper shipping name</b>   |   |
| <b>14.3. Transport hazard class(es)</b>  |   |
| <b>TRANSPORT BY INLAND WATERWAYS (ADN):</b>  |   |
| <b>14.4. Packing group</b>   |   |
| <b>14.5. Environmental hazards</b>   |   |
| <b>Transport by inland waterways notes</b>   | Not applicable.                                   |
| <b>14.6. Special precautions for user</b>  | No particular precautions.                        |
| <b>14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b> | No IBC-code for bulk transport offshore (MARPOL). |

## SECTION 15: Regulatory information

|   |   |
|---|---|
| <b>15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture</b> |   |
| <b>EU directives</b>  | EC-regulation 453/2010/EC, 1907/2006/EC (REACH), 1272/2008/EC (CLP), 790/2009/EC. Transport of dangerous goods (ADR/RID, IMDG, IATA/ICAO). Workplace exposure limits. |
| <b>15.2. Chemical safety assessment</b>   |   |
| <b>Chemical Safety Assessment</b>   | Chemical Safety Report (CSR) has not been carried out for this product.   |

## SECTION 16: Other information

|  |   |
|--|---|
| <b>Explanations to R-phrases in section 3</b>                      | R-40 Limited evidence of a carcinogenic effect.<br>R-43 May cause sensitisation by skin contact.<br>R-48/23 Toxic: danger of serious damage to health by prolonged exposure through inhalation.   |
| <b>Explanations to classification in section 3</b>                 | H317 May cause an allergic skin reaction.<br>H351 Suspected of causing cancer .<br>H372 Causes damage to organs through prolonged or repeated exposure .  |
| <b>DSD/DPD</b>   |   |
| <b>Labeling</b>  | T,  |
| <b>Risk phrases</b>  | R-40 Limited evidence of a carcinogenic effect.<br>R-43 May cause sensitisation by skin contact.<br>R-48/23 Toxic: danger of serious damage to health by prolonged exposure through inhalation.   |
| <b>Safety phrases</b>  | S-24 Avoid contact with skin.<br>S-37 Wear suitable gloves.<br>S-38 In case of insufficient ventilation, wear suitable respiratory equipment.<br>S-41 In case of fire and/or explosion do not breathe fumes.<br>S-51 Use only in well-ventilated areas. |
| <b>* Information revised since the previous version of the SDS</b> |   |
| <b>Issued by</b>   | Essenticon AS, Leif Weldingsvei 18, N-3208 Sandefjord, Norway. E-mail: post@essenticon.no Phone: +47 33 42 34 50 Fax: +47 33 42 34 59 www.essenticon.com.   |
| <b>Date of issue</b>   | 01.04.2014  |
| <b>Safety Data Sheet status</b>                                    | CLP 03 ATP  |
| <b>Signature</b>   | R. E. Lunde   |
| <b>Disclaimer</b>  | The information in this data sheet is considered to be correct according to present   |



knowledge and experience, but there is no guarantee that it is complete. It is therefore in the user's interest to ensure that the information is sufficient for the area it is intended for.